

DX330170 - 8 MM BENTLY™ COMPATIBLE PROXIMITY PROBE DRIVER FOR EDDY CURRENT PROBE, 4-20 MA OUTPUT

DX330170 - 8 mm Bently™-yhteensopiva kompakti pyörrevirta-anturi ohjain, 4-20 mA

MSP_VIRTUEMA	CTC
RT_MANUFACTURER	
MSP_VIRTUEMA	DX330170
RT_SKU:	
Herkkyy:	-7.87 V/mm
Sovellukset:	Liukulaakerin kunnonvalvonta
Halkaisija:	8 mm
Tyyppi:	4-20 mA

Saatavana erilaisilla kokoonpanoilla, kaikki asiakastilauksen pohjalta:



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ

Ordering Information

DX330170 - -

System Length	Mounting Type	Regulatory Approval
5 = 5.0 meter 9 = 9.0 meter	0 = Panel (Mounting Screws Are Not Included) 1 = DIN 2 = None	00 = CE Certified



Example Part Number: DX330170-91-00
4140 Steel, 9 meter system length, DIN mount, CE certified

MSP_VIRTUEMART_TECHDETAILS

- Temperature Range: -49 to 185°F (-45 to 85°C)
- Linear Range: 10 to 90 mils (.25 - 2.30 mm) @ approximately 4-20 mA
- Nominal Voltage Output: -200 mV/mil (-7.87 V/mm)
- 4-20 mA Output: 0.20 mA/mil
- Input Power/Voltage: 17.5 VDC to 30 VDC (Loop Powered)
- Aluminum enclosure
- Miniature 12-32 threaded connector
- 4 Position screw terminals + BNC output
- Calibrated to AISI 4140 steel

MSP_VIRTUEMART_PRODDOCS

1. [Esite](http://www.mip.fi/images/docs/fi/6_pro_dx330170_ds.pdf), (URL: http://www.mip.fi/images/docs/fi/6_pro_dx330170_ds.pdf)



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ