

# LP404 - DUAL OUTPUT SENSOR, LOOP POWER 4-20 MA, ACCELERATION, DYNAMIC ACCELERATION

LP404 - Dual Output anturi, kiihtyvyyys ja dynaaminen kiihtyvyyys, loop power, 4-20 mA

<b>MSP_VIRTUEMA</b>	CTC
<b>RT_MANUFACTURER</b>	
<b>MSP_VIRTUEMA</b>	LP404
<b>RT_SKU:</b>	
<b>Tyyppi:</b>	4-20 mA 1-akselinen
<b>Sovellukset:</b>	Condition Monitoring
<b>Taajuusalue:</b>	2.0-15000 Hz
<b>Herkkyys:</b>	100 mV/g

Saatavilla seuraavilla kokoonpanoilla:

- 3 pin liittimellä LP404 - 1B
- Integroidulla kaapelilla LP404 - 2C
- Integroidulla suojatulla kaapelilla LP404 - 3C





## MSP\_VIRTUEMART\_TECHDETAILS

- Sensitivity + 10% (100 mV/g)
- Frequency Response + 3 dB (2,0-15000 Hz)
- Power Requirement (Loop Powered) Voltage Source: 12-28 VDC
- Temperature Range: -40 to 185°F (-40 to 85°C)
- Case Material: 316L Stainless Steel

## MSP\_VIRTUEMART\_PRODDOCS

1. [Esite](http://www.mip.fi/images/docs/fi/6_pro_lp404_ds.pdf), (URL: [http://www.mip.fi/images/docs/fi/6\\_pro\\_lp404\\_ds.pdf](http://www.mip.fi/images/docs/fi/6_pro_lp404_ds.pdf))

## MSP\_VIRTUEMART\_PRODUCT\_IMAGE\_TITLE



[www.facebook.com/mipelectronics](http://www.facebook.com/mipelectronics)



[www.linkedin.com/company/mip-electronics-ltd/](http://www.linkedin.com/company/mip-electronics-ltd/)



[www.youtube.com/channel/UCpKEF\\_7bS4dMC4qPokUAgDQ](http://www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ)



[www.facebook.com/mipelectronics](https://www.facebook.com/mipelectronics)



[www.linkedin.com/company/mip-electronics-ltd/](https://www.linkedin.com/company/mip-electronics-ltd/)



[www.youtube.com/channel/UCpKEF\\_7bS4dMC4qPokUAgDQ](https://www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ)



[www.facebook.com/mipelectronics](https://www.facebook.com/mipelectronics)



[www.linkedin.com/company/mip-electronics-ltd/](https://www.linkedin.com/company/mip-electronics-ltd/)



[www.youtube.com/channel/UCpKEF\\_7bS4dMC4qPokUAgDQ](https://www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ)