

METRIX M2030-SARJAN PYÖRREVIRTA-ANTURIT

Pyörrevirta-anturi API 670 mukaisiin mittauksiin

Valmistaja: Metrix
Tuotenumero: MX2030

Metrix MX2030-sarjan anturit koostuvat 5 ja 8 mm mittausantureista. Mallit ovat saatavissa kaikilla standardin API 670 mukaisilla kierteillä. Molempien koon anturit kattavat 2 mm mittausalueen ja täyttävät täysin API 670 standardin kun niitä käytetään standardinmukaisten kaapeleiden ja laitteiden kanssa. Tarkemmat tiedot ja tuotevaihtoedot esitteestä.

Valinnaiset spesifikaatiot:

MX2030-AA-BBB-CCC-DD-EE (5mm/8mm Proximity Probe)								
MX2030 - AA					BBB	CCC	DD	EE
AA	Armor	Mount	Tip Diameter	Case Threads	Unthreaded Length	Case Length	Total Length	Agency Approval
01	No	FWD	8mm	3/8"-24	BBB = BB.B" Order in increments of 0.1" Min: 000 = 00.0" Max: case length minus 0.8" Example: 024 = 2.4"	CCC = CC.C" Order in increments of 0.1" Min: 008 = 0.8" Max: 096 = 9.6" Example: 032 = 3.2"	05 = 0.5m 10 = 1.0m 15 = 1.5m 20 = 2.0m 50 = 5.0m 90 = 9.0m	00 = None 05 = CSA, ATEX, IECEx
02	Yes	FWD	8mm	3/8"-24				
71	No	FWD	5mm	1/4"-28				
72	Yes	FWD	5mm	1/4"-28				
03	No	FWD	8mm	M10x1	BBB = BBB mm Order in increments of 10mm Min: 000 = 00mm Max: case length minus 20mm Example: 070 = 70mm	CCC = CCC mm Order in increments of 10mm Min: 020 = 20mm Max: 250 = 250mm Example: 090 = 90mm		
04	Yes	FWD	8mm	M10x1				
73	No	FWD	5mm	M8x1				
74	Yes	FWD	5mm	M8x1				
05	No	REV	8mm	3/8"-24	002 = 0.2" ONLY	012 = 1.2" ONLY		
06	No	REV	8mm	M10x1	005 = 5mm ONLY	030 = 30mm ONLY		

NOTE: All Metrix® MX2030 extension cables are part of the 10000 series part number designation for agency approvals. The 10000 series p/n will appear on the product's label along with the MX2030 p/n. e.g. MX2030-AA-BBB-CCC-DD-EE = 102AA-BBB-CCC-DD-EE

Dokumentit

- [Esite](http://www.mip.fi/images/docs/fi/MX2030.pdf), (URL: <http://www.mip.fi/images/docs/fi/MX2030.pdf>)

Lisäkuvat ja videot



