

METRIX MX8030-SARJAN PYÖRREVIRTA-ANTURIT ATEX-LUOKITUKSELLA

Pyörrevirta-anturi ATEX luokituksella

Valmistaja: Metrix
Tuotenumero: MX8030

Metrixin MX8030-sarjan pyörrevirta-anturit ovat tarkoitettu käytettäväksi vaarallisiin tiloihin. Anturit on varustettu VibeLock liittimillä ja antureita saa joko 5mm tai 8 mm halkaisijalla. Antureita on saatavissa kaikilla API 670 mukaisilla kierteillä.

Laitteen driveriksi sopii esimerkiksi Metrix MX2033. Tarkemmat tiedot ja tuotevaihtoehdot esitteestä.

MX8030-AA-BBB-CCC-DD-EE (5mm/8mm Proximity Probe with VibeLock™)								
MX8030 - AA					BBB	CCC	DD	EE
AA	Armor	Mount	Tip Diameter	Case Threads	Unthreaded Length	Case Length	Total Length	Agency Approval
01	No	FWD	8mm	3/8"-24	BBB = BB.B" Order in increments of 0.1" Min: 000 = 00.0" Max: case length minus 0.8" Example: 024 = 2.4"	CCC = CC.C" Order in increments of 0.1" Min: 008 = 0.8" Max: 096 = 9.6" Example: 032 = 3.2"	05 = 0.5 m 10 = 1.0 m 15 = 1.5 m 20 = 2.0 m 50 = 5.0 m 90 = 9.0 m	00 = None 05 = CSA, ATEX, IECEx
02	Yes	FWD	8mm	3/8"-24				
71	No	FWD	5mm	1/4"-28				
72	Yes	FWD	5mm	1/4"-28				
03	No	FWD	8mm	M10x1	BBB = BBB mm Order in increments of 10mm Min: 000 = 00mm Max: case length minus 20mm Example: 070 = 70mm	CCC = CCC mm Order in increments of 10mm Min: 020 = 20mm Max: 250 = 250mm Example: 090 = 90mm		
04	Yes	FWD	8mm	M10x1				
73	No	FWD	5mm	M8x1				
74	Yes	FWD	5mm	M8x1				
05	No	REV	8mm	3/8"-24	002 = 0.2" ONLY	012 = 1.2" ONLY		
06	No	REV	8mm	M10x1	005 = 5 mm ONLY	030 = 30 mm ONLY		

NOTE: All Metrix* MX8030 series probes and extension cables are part of the 10000 series part number designation for agency approvals. The 10000 series p/n will appear on the product's label along with the MX8030 p/n. e.g. MX8030-AA-BBB-CCC-DD-EE = 103AA-BBB-CCC-DD-EE.

Dokumentit

1. [Esite](http://www.mip.fi/images/docs/fi/MX8030.pdf), (URL: <http://www.mip.fi/images/docs/fi/MX8030.pdf>)