

TEA110 Series

Test and Measurement Accelerometer, 100mV/g, Side Exit, 10-32
Coaxial Connector, 10-32 Mounting



Actual
Product
Size
Shown




Product Features

- ▶ General Purpose Test & Measurement Accelerometer
- ▶ Lightweight Titanium Case
- ▶ 10kHz ($\pm 5\%$) Frequency Response

TEA110

Coaxial Connector


Connector Pin	Polarity
Center	(+) Signal/Power
Shell	(-) Common



Stock Product

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	TEA110		<u>Environmental</u>		
Sensitivity ($\pm 10\%$)		100 mV/g	Temperature Range	-58 to 250°F	-50 to 121°C
Frequency Response ($\pm 3\text{dB}$)	30-1,800,000 CPM	0.5 Hz-30 kHz	Maximum Shock Protection		10,000 g, peak
Frequency Response ($\pm 10\%$)	30-900,000 CPM	0.5 Hz-15 kHz	Electromagnetic Sensitivity		CE (Pending)
Frequency Response ($\pm 5\%$)	30-600,000 CPM	0.5 Hz-10 kHz	Sealing		Welded, Hermetic
Dynamic Range		$\pm 50\text{g}$, peak	<u>Physical</u>		
Non-Linearity		$\leq 1\%$	Sensing Element		PZT Ceramic
Transverse Sensitivity		$\leq 5\%$	Sensing Structure		Shear Mode
<u>Electrical</u>			Weight	0.35 oz	10 grams
Settling Time	< 2 Seconds		Case Material		Titanium
Voltage Source (IEPE)	18-30 VDC		Mounting		10-32 UNF
Constant Current Excitation	2-20 mA		Connector		10-32
Spectral Noise @ 10 Hz	30 $\mu\text{g}/\sqrt{\text{Hz}}$		Resonant Frequency	2,640,000 CPM	44 kHz
Spectral Noise @ 100 Hz	4 $\mu\text{g}/\sqrt{\text{Hz}}$		Calibration Certificate		CA12
Spectral Noise @ 1000 Hz	2 $\mu\text{g}/\sqrt{\text{Hz}}$				Step Calibration
Output Impedance	< 100 ohm				
Bias Output Voltage	10-14 VDC				
Case Isolation	Case Ground				

Typical Frequency Response



Five Year Standard Product, Two Year Custom & Private Labeled Product Warranty

www.ctconline.com | sales@ctconline.com | 585-924-5900